

# WM-70-1G

## Wall Antenna Tetra / UHF

Wall Antenna Tetra / UHF, long range antenna, 380-470 MHz, UHF

- Fullband 380-470 MHz
- Optimum performance throughout band
- Suitable for indoor/outdoor use
- Improvement of the connection in weak areas

### ELECTRICAL SPECIFICATIONS

Antenna Type	Wall Antenna Tetra / UHF
Frequency	380-470 MHz
Bandwidth	90 Mhz
Impedance	50 Ohm
VSWR	<1.5
Polarisation	Vertical
Gain	0 dBd, 2.15 dBi
Radiation Pattern	Vertical 60° / Horizontal 360°
Max. Input Power	50 W
Antistatic Protection	Direct ground (DC-short)



### MECHANICAL SPECIFICATIONS

Color	Black
Weight	500 g
Length	40 cm
Mount Type	Wall
Materials	Radome: PVC black. Support: stainless steel. Screws: stainless steel
Survival Wind Speed	37 m/s
Operating Temperature	-40 °C to +70 °C
Cable	5.0 m RG58
Connector	FME- female
Serial No.	On product label

Datasheet

2 / 2

ORDERING INFORMATION

WM-70-1G	WM-70 Antenna incl. wall bracket (packed in polybag)
----------	--