Datasheet 1 / 3

Extendr® 5G MiMo-1

High performance multiband cellular MiMo antenna with extended range

Rugged tamper-proof multiband MiMo antenna combining all major cellular bands. The antenna is ideal for fleet management, IoT and M2M applications providing a stable connection in critical areas. The antenna is offered with customer specified cables and connectors.

- Excellent performance, VSWR below 2.5 in 92% of the specified band
- IP67 water proof design for professional use
- Low profile design
- Ground plane independent



Frequency	698 -790 / 790 - 960 / 1710 - 2690 / 3300 -3800 MHz
Impedance	50 Ohm
VSWR	<4.0:1 (698-790 MHz) <3.0:1 (790-960 MHz) <1.5:1 (1710-2170 MHz, 2300-2690 MHz) <2.0:1 (3300-3800 MHz) Measured with 1.5 m cable
Isolation	> 6 dB
Polarisation	Linear
Gain	0 dBd, 2.1 dBi (698-960 MHz) 1 dBd, 3.1 dBi (790-960 MHz, 1710-2170 MHz) 3 dBd, 5.1 dBi (2300-2690 MHz, 3300-3800 MHz)
Max. Input Power	10 W
Antistatic Protection	Direct Ground (DC-short)





Printed: 11/4/2025

Datasheet

MECHANICAL SPECIFICATIONS

Color	Black
Height	46 mm (Above surface when mounted)
Weight	160 g
Diameter	Ø 111 mm
Mounting Place	On vertical or horizontal surfaces (conductive or non-conductive). E.g. car roofs, metering cabinets and brackets
Mounting hole	Ø 16 - 17 mm
Materials	ABS, silicon, brass, PVC, PE and PCB
Operating Temperature	-40°C to +85°C
Connector 1	LTE (Red): SMA-male (Other types available)
Connector 2	LTE (Red): SMA-male (Other types available)
Cable	RG174/U
Ingress protection	IP67 (when mounted)

ORDERING INFORMATION

48111-001	2 x 2.0 m cable + SMA-male
10111 001	Z X Z.O TTT Gd.D.C * ST.II Y TTT GT.C

PACKAGING INFORMATION

Туре	Bulk paking or individually packing in Polybag (See "ORDERING
	INFORMATION")

Printed: 11/4/2025

Datasheet

