WM-70-1G

Wall Antenna Tetra / UHF

Wall Antenna Tetra / UHF, long range antenna, 380-470 MHz, UHF

- Fullband 380-470 MHz
- Optimum performance throughout band
- Suitable for indoor/outdoor use
- Improvement of the connection in weak areas

ELECTRICAL SPECIFICATIONS

Antenna Type	Wall Antenna Tetra / UHF
Frequency	380-470 MHz
Bandwidth	90 Mhz
Impedance	50 Ohm
VSWR	< 1.5
Polarisation	Vertical
Gain	0 dBd, 2.15 dBi
Radiation Pattern	Vertical 60° / Horizontal 360°
Max. Input Power	50 W
Antistatic Protection	Direct ground (DC-short)

Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.

MECHANICAL SPECIFICATIONS

Color	Black
Weight	500 g
Length	40 cm
Mount Type	Wall
Materials	Radome: PVC black. Support: stainless steel. Screws: stainless steel
Survival Wind Speed	37 m/s
Operating Temperature	-40 °C to +70 °C
Cable	5.0 m RG58
Connector	FME- female
Serial No.	On product label

ORDERING INFORMATION

WM-70-1G	WM-70 Antenna incl. wall bracket (packed in polybag)

Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.