Splitter 868

Low profile 2-way Splitter

This antenna splitter is used to connect two 868 MHz antennas, easily and simply

- SMD design
- Includes three FME-female to SMA-female adapters



ELECTRICAL SPECIFICATIONS

Frequency	860 - 880 MHz
Bandwidth	20 MHz
Impedance	50 Ohm
VSWR	< 1.5:1
Max. Input Power	5 W
Insertion loss	3.5 dB
Isolation	30 dB

MECHANICAL SPECIFICATIONS

Color	Silver
Weight	60 g
Mounting	Adhesive pad Bolt-on (screws not included)
Mounting Place	Inside
Materials	Tin plated steel, pcb, brass, Teflon and PE
Operating Temperature	-40C to +70C
Connector	FME-male (All 3 ports) FME-female to SMA-female adapters included
Dimension	80 x 45 x 20 mm
Serial no.	On product label

Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.

ORDERING INFORMATION

51084-003	Individually packing in Box

PACKAGING INFORMATION

Type	Bulk packing or individually packing (See "Part No.")
Weight	Approx. 75 g



Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.