UL-706

25 Watts UHF 450 MHz Ultraplexer

- For use in repeaters and full duplex radios.
- Steel chassis with aluminium extruded cavities.
- High Q helical silver plated resonators.



ELECTRICAL SPECIFICATIONS

Type	UHF - Ultraplexer
Frequency	L: 400 - 440 MHz H: 440 - 475 MHz
Spacing	10 MHz
Insertion loss	≤ 1.5 dB
Isolation (Suppresion)	Single channel ≥ 75 dB
VSWR	≤ 1:1.5
Impedance	50 Ohm
Maximum Input Power	25 Watts
Frequency Stability	9 ppm/°C (approx.)

MECHANICAL SPECIFICATIONS

Color	Aluminum
Dimension	50 x 156 x 40 mm
Weight	0.4 kg
Operating Temperature	-30°C to +60°C
Connector	SMA-female
Serial no.	On product label

Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.

ORDERING INFORMATION

UL-7062-L	L: 400-440 MHz, 10 MHz Not tuned
UL-7062-H	H: 440-475 MHz, 10 MHz Not tuned

Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.