FRPT-3

VHF 100 MHz 150 Watts Helical Band-Pass/Band-Reject Filter

- For use in repeaters and full duplex radios.
- Steel chassis with teflon isolators and aluminium extruded cavities.
- High Q helical silver plated resonators.
- Easy tuning.
- FRPT-333: 3 resonators

ELECTRICAL SPECIFICATIONS

Type	FM - Helical Band-Pass/Band-Reject Filter
Frequency	88-108 MHz
Pass-Reject Spacing	≥ 2.0 MHz
Insertion Loss	≤ 1.0 dB
Attenuation	≥ 60 dB
VSWR	≤ 1:1.5
Impedance	50 Ohm
Maximum Input Power	150 Watts
Frequency Stability	9 ppm/°C (approx.)

MECHANICAL SPECIFICATIONS

Color	Black Grey (RAL7021)
Dimension	245 x 155 x 33 mm
Weight	1.0 kg
Operating Temperature	-30°C to +60°C
Connector	Type N-female
Serial no.	On product label

ORDERING INFORMATION

FRPT-333	Not tuned In Box

Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.

Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.