Datasheet

# DC-70-150

## UHF 450 MHz Cavity Duplex Filter

- High Power Cavity Duplex Filter
- For use in repeaters, full duplex radios and base stations.
- Four or six Cavities 150 mm (5 ") Cavity size.
- High Q Small Duplex Spacing
- Easy tuning.

### **ELECTRICAL SPECIFICATIONS**

| Туре                      | UHF - Cavity Duplex Filter   |
|---------------------------|--|
| Model                     | DC-70AQ - Four Cavities DC-70AQS - Six Cavities                    |
| Frequency                 | 380-512 MHz  |
| Spacing                   | DC-70AQ: > 1.0 MHz<br>DC-70AQS: > 2.0 MHz                          |
| Insertion loss            | DC-70AQ: < 1.5 dB<br>DC-70AQS: < 2.0 dB                            |
| Isolation<br>(Suppresion) | DC-70AQ: Single channel ≥ 70dB<br>DC-70AQS: Single channel ≥ 80 dB |
| VSWR                      | ≤ 1:1.5  |
| Impedance                 | 50 Ohm   |
| Maximum Input<br>Power    | 150 Watts  |
| Frequency Stability       | 0.9 ppm/°C (approx.)   |





Printed: 8/11/2025

Datasheet

#### **MECHANICAL SPECIFICATIONS**

| Color                    | Black Grey (RAL7021)  |
|--------------------------|---|
| Dimension                | DC-70AQ: 400 x 300 x 300 mm<br>DC-70AQS: 400 x 450 x 300 mm |
| Weight                   | DC-70AQ: 10.0 kg<br>DC-70AQS: 15.0 kg                       |
| Operating<br>Temperature | -30°C to +60°C  |
| Connector                | Type N-female   |
| Serial no.               | On product label  |

### ORDERING INFORMATION

| DC-70AQ  | Four Cavities - Not tuned In Box   |
|----------|------------------------------------|
| DC-70AQS | Six Cavities - Not tuned<br>In Box |

