Printed: 10/21/2025

Datasheet

BC4-1G

VHF Low 80 MHz Unity Gain Omni Base Station Antenna

This meticulously constructed base station antenna with integrated multipurpose mounting bracket comes with a generous bandwidth which reduces the need for multiple antennas both in stock and on installation sites.

• No groundplane needed

ELECTRICAL SPECIFICATIONS

Antenna Type	Half Wave Dipole
Frequency	66 - 78 MHz, 76 - 88 MHz (L/H)
Bandwidth	12 MHz
Impedance	50 ohm
Vswr	< 1.5:1
Polarisation	Vertical
Gain	0 dBd, 2.15 dBi
Radiation Pattern	Omni Directional (Horizontal)
Half Power Beamwidth	80°
Max. Input Power	150 W
Antistatic Protection	Direct Ground



Printed: 10/21/2025

Datasheet

MECHANICAL SPECIFICATIONS

Color	White and Silver
Length	3000 mm
Weight	6.0 kg
Mount type	Fixed Tube Mounting Bracket. Stainless Steel Mounting Hardware included.
Mounting Place	On vertical mast tube; Ø 30- 60 mm
Materials	Brass, Copper, Fibreglass and Aluminium
Survival Wind Speed	45 m/s
Operating Temperature	-55C to +70C
Connector	Type N-female
Ingress protection	IP66
Serial no.	On product label

ORDERING INFORMATION

BC4-1GL	66 - 78 MHz Individually packing in Carton tube
BC4-1GH	76 - 88 MHz Individually packing in Carton tube

PACKAGING INFORMATION

Туре	See "Part No."
------	----------------

Printed: 10/21/2025

Datasheet

