



## Datasheet

2 / 2

## MECHANICAL SPECIFICATIONS

|                       |  |
|-----------------------|--|
| Color                 | Black  |
| Dimension             | 482.6 x 133.5 x 500 mm (W x H x L)               |
| Weight                | Single isolator: 8.0 kg<br>Dual isolator: 8.6 kg |
| Connector             | Type N-female                                    |
| Serial no.            | On product label                                 |
| Operating temperature | -20° to +60°C                                    |

## ORDERING INFORMATION

|           |   |
|-----------|---|
| 55432-013 | HCMR450-3S-L-5<br>400-440 MHz 3CH x 50 W Single Isolator + DU-5   |
| 55434-023 | HCMR450-3S-L-10<br>400-440 MHz 3CH x 50 W Single Isolator + DU-10 |
| 55432-033 | HCMR450-3S-H-5<br>440-475 MHz 3CH x 50 W Single Isolator + DU-5   |
| 55434-043 | HCMR450-3S-H-10<br>440-475 MHz 3CH x 50 W Single Isolator + DU-10 |
| 55432-053 | HCMR450-3D-L-5<br>400-440 MHz 3CH x 50 W Dual Isolator + DU-5     |
| 55434-063 | HCMR450-3D-L-10<br>400-440 MHz 3CH x 50 W Dual Isolator + DU-10   |
| 55432-073 | HCMR450-3D-H-5<br>440-475 MHz 3CH x 50 W Dual Isolator + DU-5     |
| 55434-083 | HCMR450-3D-H-10<br>440-475 MHz 3CH x 50 W Dual Isolator + DU-10   |
| Note      | Power cable not included  |