

Datasheet

2 / 2

MECHANICAL SPECIFICATIONS

Color	Black Grey (RAL7021)
Dimension	Two units: 482.6 x 89.0 x 300 mm (W x H x L) One unit: 482.6 x 44.5 x 300 (W x H x L)
Weight	Single isolator: 10.3 kg Dual isolator: 11.9 kg
Connector	Type N-female
Serial no.	On product label
Operating temperature	-20° to +60°C

ORDERING INFORMATION

55142-113	HCMR150-4S-L-5-150 144-162 MHZ 4CH x 100 W Single Isolator + DUPT-5 2 x 2HU + 1 x 1HU
55144-123	HCMR150-4S-L-10-150 144-162 MHZ 4CH x 100 W Single Isolator + DUPT-10 2 x 2HU + 1 x 1HU
55142-133	HCMR150-4S-H-5-150 158-175 MHZ 4CH x 100 W Single Isolator + DUPT-5 2 x 2HU + 1 x 1HU
55144-143	HCMR150-4S-H-10-150 158-175 MHZ 4CH x 100 W Single Isolator + DUPT-10 2 x 2HU + 1 x 1HU
55142-153	HCMR150-4D-L-5-150 144-162 MHZ 4CH x 100 W Dual Isolator + DUPT-5 2 x 2HU + 1 x 1HU
55144-163	HCMR150-4D-L-10-150 144-162 MHZ 4CH x 100 W Dual Isolator + DUPT-10 2 x 2HU + 1 x 1HU
55142-173	HCMR150-4D-H-5-150 158-175 MHZ 4CH x 100 W Dual Isolator + DUPT-5 2 x 2HU + 1 x 1HU
55144-183	HCMR150-4D-H-10-150 158-175 MHZ 4CH x 100 W Dual Isolator + DUPT-10 2 x 2HU + 1 x 1HU
Note	Power cable not included