

## Datasheet

1 / 3

# BA-IN

## Mobile roof base mount

Strong and reliable universal base mount for mobile applications. It accepts antenna whips with internal M10 threaded stud.

- Compatible with WIN series antenna whips
- Universal Mounting

## ELECTRICAL SPECIFICATIONS

Frequency	66 - 512 MHz
Impedance	50 Ohm
Max. Input Power	50 W



## MECHANICAL SPECIFICATIONS

Color	Black
Weight	255 g
Diameter	Ø 50 mm
Mounting	Bolt-on (From inside)
Mounting Place	On vehicle roof, trunk or wing
Height above roof	35 mm
Mounting hole	Ø 11mm
Build-in Depth	Approx. 12 mm
Materials	ABS, chromed brass, chromed stainless steel and rubber
Operating Temperature	-40 to +70°C
Cable	See "ORDERING INFO" (Other lengths available)
Ingress protection	IP65 (When mounted)

## ORDERING INFORMATION

BA-IN	Base IN - M10 cable 5 m RG-58 - no connector
BA-IN-6	Base IN - M10 cable 6 m RG-58 - no connector
BA-IN-7	Base IN - M10 cable 7 m RG-58 - no connector
BA-IN-8	Base IN - M10 cable 8 m RG-58 - no connector
BA-IN-9	Base IN - M10 cable 9 m RG-58 - no connector
BA-IN-10	Base IN - M10 cable 10 m RG-58 - no connector
BA-IN-11	Base IN - M10 cable 11 m RG-58 - no connector
BA-IN-12	Base IN - M10 cable 12 m RG-58 - no connector
BA-IN-15	Base IN - M10 cable 15 m RG-58 - no connector

## PACKAGING INFORMATION

Type	Bag
------	-----

