

Datasheet

BA-IN

Mobile roof base mount

Strong and reliable universal base mount for mobile applications. It accepts antenna whips with internal M10 threaded stud.

- Compatible with WIN series antenna whips
- Universal Mounting

ELECTRICAL SPECIFICATIONS

| | |
|------------------|--------------|
| Frequency | 66 - 512 MHz |
| Impedance | 50 Ohm |
| Max. Input Power | 50 W |



MECHANICAL SPECIFICATIONS

| | |
|-----------------------|--|
| Color | Black |
| Weight | 255 g |
| Diameter | Ø 50 mm |
| Mounting | Bolt-on (From inside) |
| Mounting Place | On vehicle roof, trunk or wing |
| Height above roof | 35 mm |
| Mounting hole | Ø 11mm |
| Build-in Depth | Approx. 12 mm |
| Materials | ABS, chromed brass, chromed stainless steel and rubber |
| Operating Temperature | -40 to +70°C |
| Cable | See "ORDERING INFO" (Other lengths available) |
| Ingress protection | IP65 (When mounted) |

Datasheet

ORDERING INFORMATION

| | |
|----------|---|
| BA-IN | Base IN - M10 cable 5 m RG-58 - no connector |
| BA-IN-6 | Base IN - M10 cable 6 m RG-58 - no connector |
| BA-IN-7 | Base IN - M10 cable 7 m RG-58 - no connector |
| BA-IN-8 | Base IN - M10 cable 8 m RG-58 - no connector |
| BA-IN-9 | Base IN - M10 cable 9 m RG-58 - no connector |
| BA-IN-10 | Base IN - M10 cable 10 m RG-58 - no connector |
| BA-IN-11 | Base IN - M10 cable 11 m RG-58 - no connector |
| BA-IN-12 | Base IN - M10 cable 12 m RG-58 - no connector |
| BA-IN-15 | Base IN - M10 cable 15 m RG-58 - no connector |

PACKAGING INFORMATION

| | |
|------|-----|
| Type | Bag |
|------|-----|

Datasheet

3 / 3

