

WIN-4 Series

VHF (66 - 134 MHz) Mobile Whip

The WIN-4 series offers several whip to be used for the VHF band, specifically 66 - 134 MHz.

All antenna whips are made of stainless steel, black chromed to withstand the harshest conditions.

- WIN-4 - $\lambda/4$ antenna whip
- WIN-4M - $\lambda/4$ antenna whip with a conical spring
- WIN-4R - $\lambda/4$ antenna whip with adjustable tilt
- WIN-4RM - $\lambda/4$ antenna whip with adjustable tilt and conical spring

ELECTRICAL SPECIFICATIONS

Type	Whip antenna ($\lambda/4$)
Frequency	66 - 134 MHz
Bandwidth	3% of f.res (VSWR \leq 1.5:1)
VSWR	\leq 1.3:1 @ f.res
Impedance	50 Ohm
Polarisation	Vertical
Gain	0 dBd, 2.15 dBi
Max. Input Power	50 W



Datasheet

2 / 4

MECHANICAL SPECIFICATIONS

Color	Black
Length	WIN-4: 1320 mm WIN-4M/R: 1380 mm WIN-4RM: 1440 mm
Weight	Approx. 115 g
Mounting	On BA-IN base
Mounting Place	Vehicle roof (Metalic surface)
Mounting Instructions	Antenna Whip must be cut to specified frequency.
Materials	Chromed brass and stainless steel
Operating Temperature	-40 to +70°C
Connector	M10 Thread


ORDERING INFORMATION

WIN-4	$\lambda/4$ Whip
WIN-4M	$\lambda/4$ whip with a conical spring
WIN-4R	$\lambda/4$ whip with adjustable tilt
WIN-4RM	$\lambda/4$ whip with adjustable tilt and conical spring


PACKAGING INFORMATION

Type	In Bag
------	--------







Measured on a \varnothing 500 mm ground plane



Measured on a \varnothing 500 mm ground plane



Measured on a \varnothing 500 mm ground plane



Measured on a \varnothing 500 mm ground plane