

GPS-976

Four in One Multiband Antenna (UHF, Cellular, WLAN, GNSS) with Unity Gain Whip

Roof mounted four in one combination antenna base with UHF, Cellular, WLAN and Active GNSS. High quality compact construction desinged for through hole mounting.

- Unity Gain UHF Whip
- Multiple bands in one installation
 - UHF (Tetra, PMR)
 - Cellular (GSM, UMTS, LTE, 5G NR)
 - WLAN (IEEE 802.11 a/b/g/h/j/n/p/ac)
 - GNSS (GLONASS, GPS, Galileo and BeiDou)

ELECTRICAL SPECIFICATIONS

Type	Combination Antenna
Frequency	380 - 410 MHz (UHF) 790-960 MHz, 1710-2690 MHz (Cellular) 2400-2485 MHz, 5250-5850 MHz (WLAN) 1552 - 1608 MHz (GNSS)
Bandwidth	See 'FREQUENCY'
VSWR	≤1.8:1 (UHF), ≤3.3:1 (Cellular), ≤2.0:1 (WLAN)
Impedance	50 Ohm
Polarisation	Linear (UHF, Cellular, WLAN), RHC (Right Hand Circular)(GNSS)
Gain	0 dBd, 2.15 dBi (UHF, Cellular, WLAN)
Satellite System	GLONASS, GPS, Galileo and BeiDou
LNA Gain	18 dB @ 2.7 VDC 22 dB @ 5.0 VDC
Noise Figure	Min. 1.7 dB Max. 2.1 dB
Supply Voltage	2.7 - 5.1 VDC
Current Consumption, Average	10 mA @ 2.7 VDC 16 mA @ 5.0 VDC
Max. Input Power	10 W



Datasheet

2 / 2

MECHANICAL SPECIFICATIONS

Color	Black
Dimensions	95 x 52 x 95 mm
Weight	180 g
Mounting	Bolt-on
Mounting Place	On vertical or horizontal surfaces (conductive). E.g. car roofs, metering cabinets and brackets
Mounting Hole	15 x 15 mm or Ø 19.0 mm
Materials	PA, Rubber, SS, Copper, Brass, PCB (TBC)
Operating Temperature	-30 to +80°C
Connector	FME-male (UHF, Cellular), SMA-male (WLAN, GNSS)
Cable	180 mm RG-316 (UHF), 140 mm RG-174 (Cellular), 220 mm RG-174 (WLAN), 210 mm RG-174 (GNSS)
Ingress Protection	IP65 (when mounted)
Serial No.	On product label

ORDERING INFORMATION

GPS-976	Antenna - In polybag
---------	----------------------