

# GPS-776

## 3-in-1 Multiband Antenna (UHF/Cellular/GNSS) with Unity Gain Whip

Roof mounted 3-in-1 combination antenna base with UHF Unity Gain whip antenna and with integrated active GNSS antenna and Cellular

- Unity Gain UHF Whip
- Multiple bands in one installation
  - Tetra
  - GSM/UMTS/LTE
  - GLONASS/GPS/Galileo/BeiDou
- High quality compact construction

### ELECTRICAL SPECIFICATIONS

Frequency	380-430 MHz, 824-960 MHz, 1710 -2170 MHz, 1552 - 1608 MHz (UHF/Cellular/GNSS)
Bandwidth	20 MHz in UHF See "FREQUENCY" (Cellular, GNSS)
Impedance	50 Ohm
V.S.W.R	≤1.3 @ f.res (380-430 MHz), ≤2.5 (1552-1608 MHz), ≤3.3 (824-960/1710-2170 MHz)
Satellite System	GLONASS, GPS, Galileo and BeiDou
Polarization	Linear (UHF, Cellular), Right Hand Circular (RHC) (GNSS)
Gain	0 dBd, 2.15 dBi (UHF)
Max. Input Power	15 W (UHF), 10 W (Cellular)
LNA Gain	18±1 dB @ 2.7 VDC 22±1 dB @ 5.0 VDC
Noise Figure	Max. 2.1 dB
Voltage	2.7-5.0 VDC
Current Consumption, Average	12 mA @ 2.7 VDC 26 mA @t 5.0 VDC



## Datasheet

2 / 2

## MECHANICAL SPECIFICATIONS

Color	Black
Weight	600 g
Dimensions	95 x 52 x 230 mm
Mounting	Bolt-on
Mounting Hole	15x15 mm or Ø 19 mm
Build-In Depth	TBA mm
Materials	PA, PCB, PE, copper, brass and stainless steel
Operating Temperature	-30 to +80 °C
Cable	180 mm RG316/U (UHF), 130 mm RG174/U (Cellular), 210 mm RG174/U (GNSS)
Connector	TNC-male (UHF), FME-female (Cellular), SMA-male (GNSS)
Ingress Protection	IP65 (when mounted)
Serial No.	On product label

## ORDERING INFORMATION

GPS-776	In Bag
---------	--------