Printed: 12/3/2025

Datasheet

TELESAT-6

Rugged low-profile multiband antenna with built-in active GNSS antenna

Heavy duty omni-directional 6-BAND antenna including built-in active GNSS antenna for tracking and navigation purpose. Through-hole roof mounting on trucks, trailers etc.

- LOW PROFILE DESIGN
- NO GROUNDPLANE NEEDED
- 6 BANDS IN ONE INSTALLATION



ELECTRICAL SPECIFICATIONS

790 - 960 MHz, 1561.1 - 1605.4 MHz, 1710 - 2170 MHz, 2500 - 2690 MHz (GSM850/900/1800/1900/UMTS/LTE/GNSS)
< 4.0:1 (790-960 MHz), < 5.0:1 (1710-2170 MHz), < 9.0:1 (2500-2690 MHz)
50 ohm
GLONASS, GPS, Galileo and BeiDou
Linear
0 dBi (Cellular)
10 W (GSM/3G)
26 dB (GNSS)
1.35 dB (GNSS)
3 - 5.5 V DC (Fed via cable) (GNSS)
20 mA



Printed: 12/3/2025

Datasheet

MECHANICAL SPECIFICATIONS

Color	Black
Height	16 mm
Weight	125 g
Diameter	Ø 92 mm
Mounting	Bolt-on with adhesive tape for effective sealing
Mounting Place	On horizontal surface (Max. panel thickness 3 mm with cables to the side or 12 mm with cables straight out of the antenna)
Mounting Instruction	Unobstructed view to satellites
Mounting hole	Ø 13 - 20 mm
Build-in Depth	Approx. 17 mm
Materials	ABS, PE, brass and PCB
Operating Temperature	-40°C to +70°C
Connector	GSM/UMTS: SMA-female (Red)
Connector2	GNSS: FME-female (Blue)
Cable	150 - 200 mm
Ingress protection	IP65 (When mounted)

ORDERING INFORMATION

P/N	45600IP (Bulk packing)
P/N	45600 (Individually packing in Polybag)

PACKAGING INFORMATION

Type Bulk packing or individually packing in F	olybag (See "Part No.")
--	-------------------------

Printed: 12/3/2025

Datasheet

