

Datasheet

GP60-500 1/4 X 0DB

Full length factory tuned Ground Plane Antenna

- Full omni-directional radiation pattern
- Factory tuned to customer specified frequency
- NO GROUNDPLANE NEEDED

ELECTRICAL SPECIFICATIONS

Frequency	60 - 500 MHz (Please specify Centre-Frequency (CF) within these frequencies)
Bandwidth	4 % of the specified Centre-Frequency (CF)
Impedance	50 ohm
Vswr	<1.5
Polarisation	Vertical
Gain	0 dBd, 2.1 dBi
Max. Input Power	400 W

MECHANICAL SPECIFICATIONS

Color	White
Height	Max. 2200 mm (dep. on frequency)
Weight	1100 g
Mounting	On pole Ø 38 mm (Not supplied)
Mounting Place	On tower etc.
Materials	Chrome plated brass and PU-painted glass-fibre radiator and radials Ø 8 mm
Operating Temperature	-40C to +70C
Connector	UHF-female
Cable	No cable supplied
Ingress Protection	IP66

ORDERING INFORMATION

P/N	11023X
-----	--------



Datasheet

PACKAGING INFORMATION

Type	Individually packing in Polybag
Size	Max. 1.35 m (Depending on frequency)

