

CL4M/M (FME)

Semi-flexible reduced 1/4 λ centre-loaded portable whip antenna

Semi-flexible reduced 1/4 λ portable whip antenna with integrated FME-female connector adapter system for universal fitting, made for use on transceivers.

- FME CONNECTOR ADAPTER SYSTEM FOR UNIVERSAL FITTING

ELECTRICAL SPECIFICATIONS

Frequency	72 - 82 MHz (4M-BAND)
Bandwidth	10 MHz
Impedance	50 ohm
Vswr	< 2.0 @ f.res.
Polarisation	Vertical
Gain	0 dBD, 2.1 dBi
Max. Input Power	50 W



MECHANICAL SPECIFICATIONS

Color	Black
Height	Approx. 465 mm
Weight	30 g
Mounting Place	On transceivers
Materials	PC, glass-fibre, copper, PE and brass
Operating Temperature	-40C to +70C
Connector	FME-female



Datasheet

2 / 2

ORDERING INFORMATION

P/N	14109 (Antenna whip only)
P/N	14109IP (Antenna whip only - Bulk packing)
P/N	14121 (Antenna + BNC-male adapter)
P/N	14121IP (Antenna + BNC-male adapter - Bulk packing)
P/N	14122 (Antenna + TNC-male adapter)
P/N	14122IP (Antenna + TNC-male adapter - Bulk packing)

PACKAGING INFORMATION

Type	Polybag or bulk
	