Printed: 10/21/2025

Datasheet

# PT420 1/4 (FME)

# Flexible full 1/4 λ whip antenna with FME-connector

Flexible full 1/4  $\lambda$  TITANIUM whip antenna with integrated FME-connector, especially made for use on portable transceivers. In order to install the antenna on various transceivers a wide range of connector adapters are available (not included)

- FME CONNECTOR ADAPTER SYSTEM FOR UNIVERSAL FITTING
- TITANIUM ALLOY RADIATING ELEMENT

## **ELECTRICAL SPECIFICATIONS**

Frequency	400 - 450 MHz (TETRA)
Bandwidth	50 MHz
Impedance	50 ohm
Vswr	< 2.0 @ f.res.
Polarisation	Vertical
Gain	0 dBd, 2.1 dBi
Max. Input Power	50 W

#### MECHANICAL SPECIFICATIONS

Color	Black
Height	Approx. 181 mm
Weight	15 g
Mounting Place	On transceivers etc.
Materials	POM, PE, Titanium alloy and brass
Operating Temperature	-40C to +70C
Connector	FME-female

Printed: 10/21/2025

Datasheet

## ORDERING INFORMATION

P/N	14108 (Antenna whip only)
P/N	14108IP (Antenna whip only - Bulk packing)
P/N	14211 (Antenna + TNC-male adapter)
P/N	14211IP (Antenna + TNC-male adapter - Bulk packing)
P/N	14208 (Antenna + BNC-male adapter)
P/N	14208IP (Antenna + BNC-male adapter - Bulk packing)

# PACKAGING INFORMATION