

# PT900 1/2 (FME)

Flexible 1/2 λ whip antenna with FME-connector

Super-flexible 1/2 λ TITANIUM whip antenna with integrated FME-connector, especially made for use on portable and stationary applications in the GSM900 band. In order to install the antenna on various transceivers a wide range of connector adapters are available (not included)

- FME Connector Adapter System for Universal Fitting
- TITANIUM alloy Radiating Element

## ELECTRICAL SPECIFICATIONS

Frequency	860 - 960 MHz (GSM900, ISM)
Bandwidth	100 MHz
Impedance	50 ohm
Vswr	< 2.0 @ f.res.
Polarisation	Vertical
Gain	0 dBd, 2.1 dBi
Max. Input Power	25 W



## MECHANICAL SPECIFICATIONS

Color	Black
Height	Approx. 180 mm
Weight	25 g
Mounting Place	On transceivers and modems etc.
Materials	POM, PE, Titanium alloy and brass
Operating Temperature	-40C to +70C
Connector	FME-female

Datasheet

ORDERING INFORMATION

P/N	14017 (Antenna whip only)
P/N	14017IP (Antenna whip only - Bulk packing)
P/N	14311 (Antenna + TNC-male adapter)
P/N	14311IP (Antenna + TNC-male adapter - Bulk packing)

PACKAGING INFORMATION

Type	Polybag or bulk
------	-----------------

