Datasheet

PT2400 1/4 (SMA)

Semi-flexible full 1/4 \(\lambda \) whip antenna with SMA-connector

Semi-flexible full 1/4 λ whip antenna with integrated SMA-male connector, especially made for portable and stationary wireless applications (M2M) in WLAN systems

ELECTRICAL SPECIFICATIONS

| Frequency | 2310 - 2485 MHz (WLAN, BLUETOOTH, ZIGBEE) |
|------------------|---|
| Bandwidth | 175 MHz |
| Impedance | 50 ohm |
| Vswr | < 2.0 @ f.res. |
| Polarisation | Vertical |
| Gain | 0 dBd, 2.1 dBi |
| Max. Input Power | 10 W |



MECHANICAL SPECIFICATIONS

| Color | Black |
|----------------|------------------------------|
| Height | 43 mm |
| Weight | 6 g |
| Mounting Place | On modems etc. |
| Materials | PE, copper, brass and Teflon |
| Connector | SMA-male |

ORDERING INFORMATION

| P/N | 14350 |
|-----|------------------------|
| P/N | 14350IP (Bulk-packing) |

PACKAGING INFORMATION

| Type Bulk or Polybag | |
|----------------------|--|
|----------------------|--|

Printed: 8/4/2025

Datasheet



