

PT920 1/2 (SMA)

Semi-flexible full 1/2 λ multiband whip antenna with SMA-connector

Semi-flexible full 1/2 λ multiband whip antenna with integrated SMA-male connector, especially made for portable and stationary wireless applications (M2M) for cellular systems.

- FOR CELLULAR TRANSCEIVERS: GSM (2G), UMTS (3G), LTE (4G) & 5G NR (5G).

ELECTRICAL SPECIFICATIONS

Frequency	880 - 960 MHz, 1710 - 1880 MHz, 1850 - 1990 MHz, 1920 - 2170 MHz (GSM900/1800/1900/UMTS/DECT)
Bandwidth	See "FREQUENCY"
Impedance	50 ohm
Vswr	< 2.0 @ f.res.
Polarisation	Vertical
Gain	0 dBd, 2.1 dBi
Max. Input Power	10/5 W



MECHANICAL SPECIFICATIONS

Color	Black
Height	160 mm
Weight	15 g
Mounting Place	On modems etc.
Materials	PE, copper, brass and Teflon
Connector	SMA-male

ORDERING INFORMATION

P/N	14421
P/N	14421IP (Bulk-packing)

Datasheet

PACKAGING INFORMATION

Type	Bulk or Polybag
------	-----------------

