

# MINI-PT QUAD 1/4 (SMA)

Semi-flexible full  $1/4 \lambda$  multiband whip antenna with SMA-connector

Semi-flexible full  $1/4 \lambda$  multiband whip antenna with integrated SMA-male connector, especially made for portable and stationary wireless applications (M2M) for cellular and DECT systems

## ELECTRICAL SPECIFICATIONS

Frequency	824 - 894 MHz, 890 - 960 MHz, 1710 - 1880 MHz, 1850 - 1990 MHz (GSM850/900/1800/1900/DECT)
Bandwidth	See "FREQUENCY"
Impedance	50 ohm
Vswr	< 2.0 @ f.res.
Polarisation	Vertical
Gain	0 dBd, 2.1 dBi
Max. Input Power	10/5 W



## MECHANICAL SPECIFICATIONS

Color	Black or grey
Height	42.5mm
Weight	6 g
Diameter	12.3mm
Mounting Place	On modems etc.
Materials	PE, copper, brass and Teflon
Connector	SMA-male

## ORDERING INFORMATION

P/N	14918 (Black)
P/N	14918IP (Black - Bulk-packing)
P/N	14918GIP (Grey - Bulk-packing)

PACKAGING INFORMATION

Type	Bulk or Polybag
------	-----------------

