HE425 (ICOM-SMA)

Flexible Helical whip antenna with ICOM style SMA connector

Flexible Helical whip antenna with integrated Icom SMA style connector, made for use on ICOM portable transceivers



ELECTRICAL SPECIFICATIONS

Frequency	410 - 440 MHz (TETRA)
Bandwidth	30 MHz
Impedance	50 ohm
Vswr	< 2.0 @ f.res.
Polarisation	Vertical
Gain	0 dBd, 2.1 dBi
Max. Input Power	50 W

MECHANICAL SPECIFICATIONS

Color	Black
Height	Approx. 72 mm
Weight	18 g
Mounting Place	On Icom transceivers
Materials	POM, PE, steel and brass
Operating Temperature	-40C to +70C
Connector	Icom SMA style connector

ORDERING INFORMATION

P/N	14516 (Antenna whip only)
P/N	14516IP (Antenna whip only - Bulk packing)

Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.

PACKAGING INFORMATION

Type	Bulk or Polybag



Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.