

# E135-300 0 dB RIGID (M6)

Rigid full 1/4  $\lambda$  customer tunable antenna whip

Customer tunable antenna whip especially made for use with SX-Mount and Multimag on vehicle roof etc.

- CUSTOMER TUNABLE (BY CUTTING)
- [CUTTING TABLE](#) FOR TUNING SUPPLIED

## ELECTRICAL SPECIFICATIONS

Frequency	135 - 300 MHz (2M-BAND)
Bandwidth	20 MHz
Impedance	50 ohm
Vswr	< 2.0
Polarisation	Vertical
Gain	0 dBd, 2.1 dBi
Max. Input Power	100 W



## MECHANICAL SPECIFICATIONS

Color	Black
Height	Approx. 515 mm (Before cutting)
Weight	28 g
Mounting	On "E"-type mounts
Mounting Place	Vehicle roof
Mounting Instruction	Antenna must be cut to specified frequency. Cutting Table included
Materials	Stainless steel, PE and brass
Operating Temperature	-40C to +70C
Connector	M6 Internal thread

## Datasheet

2 / 2

## ORDERING INFORMATION

P/N	E12044
P/N	E12044IP (Bulk packing)

## PACKAGING INFORMATION

Type	Polybag or bulk
	