

E66-88DKF 0 dB (M6)

Mobile reduced $1/4 \lambda$ spring loaded customer tunable antenna whip

Flexible spring loaded customer tunable antenna whip especially made for use with SX-Mount and Multimag on vehicle roof etc. The antenna comes with 3 different lengths of topsections for easy tuning in the entire 4 m band

- Easy tuning in the specified frequency band

ELECTRICAL SPECIFICATIONS

| | |
|------------------|----------------|
| Frequency | 66 - 88 MHz |
| Frequency | 66 - 88 MHz |
| Bandwidth | 4 MHz |
| Impedance | 50 ohm |
| Vswr | < 2.0 |
| Polarisation | Vertical |
| Gain | 0 dBd, 2.1 dBi |
| Max. Input Power | 100 W |



MECHANICAL SPECIFICATIONS

| | |
|-----------------------|--|
| Color | Black |
| Height | Approx. 395-560 mm (Dep. on frequency) |
| Weight | 115 g |
| Mounting | On "E"-type mounts |
| Mounting Place | Vehicle roof |
| Materials | Stainless steel, glass-fibre, copper, PE and brass |
| Operating Temperature | -40C to +70C |
| Connector | M6 Internal thread |

Datasheet

ORDERING INFORMATION

| | |
|-----|-------------------------|
| P/N | E12247 |
| P/N | E12247IP (Bulk packing) |

PACKAGING INFORMATION

| | |
|------|-----------------|
| Type | Polybag or bulk |
|------|-----------------|

