

E40DKF 0 dB (M6)

Mobile spring loaded reduced 1/4 λ antenna whip (40 MHz)

Mobile spring loaded reduced 1/4 λ antenna whip especially made for use in connection with SX-Mount and Multimag on vehicle roof etc.

ELECTRICAL SPECIFICATIONS

| | |
|--------------|----------------|
| Frequency | 40 - 41 MHz |
| Bandwidth | 1 MHz |
| Impedance | 50 ohm |
| Vswr | <2 |
| Polarisation | Vertical |
| Gain | 0 dBd, 2.1 dBi |
| Bandwidth | 50 W |



MECHANICAL SPECIFICATIONS

| | |
|-----------------------|--|
| Color | Black |
| Height | Approx. 485 mm |
| Weight | 105 g |
| Mounting | On "E"-type mounts |
| Mounting Place | Vehicle roof |
| Materials | Stainless steel, glass-fibre, copper, PE and brass |
| Operating Temperature | -40C to +70C |
| Connector | M6 Internal thread |

ORDERING INFORMATION

| | |
|-----|-------------------------|
| P/N | E12246 |
| P/N | E12246IP (Bulk packing) |

PACKAGING INFORMATION

| Type | Bulk or Polybag |
|------|-----------------|
|------|-----------------|

