Printed: 10/28/2025

Datasheet

# G135-300 0 dB RIGID (M5)

Rigid full  $1/4 \lambda$  customer tunable antenna whip (135-300 MHz)

Rigid customer tunable antenna whip especially made for use with "G"-type mounts (bases) on vehicle roof etc.

- CUSTOMER TUNABLE (BY CUTTING)
- CUTTING TABLE FOR TUNING SUPPLIED

#### **ELECTRICAL SPECIFICATIONS**

Frequency	135 - 300 MHz (2M-BAND)
Bandwidth	15 MHz
Impedance	50 ohm
Vswr	< 2.0
Polarisation	Vertical
Gain	0 dBd, 2.1 dBi
Max. Input Power	200 W

### MECHANICAL SPECIFICATIONS

Color	Black
Height	Approx. 510 mm (Before cutting)
Weight	30 g
Mounting	On "G"-type mounts
Mounting Place	Vehicle roof
Mounting Instruction	Antenna must be cut to specified frequency. Cutting Table included
Materials	Ctain loss stool DE and brees
Materials	Stainless steel, PE and brass
Operating Temperature	-40C to +70C

Printed: 10/28/2025

## Datasheet

#### ORDERING INFORMATION

P/N	G12050
P/N	G12050IP (Bulk packing)

### PACKAGING INFORMATION

