

# G135-300F 0 dB RIGID (M5)

Rigid spring loaded 1/4  $\lambda$  tunable whip for G-Mount (135-300 MHz)

Rigid spring loaded customer tunable antenna whip especially made for use with "G"-type mounts (bases) on vehicle roof etc.

- CUSTOMER TUNABLE (BY CUTTING)
- CUTTING TABLE FOR TUNING SUPPLIED

## ELECTRICAL SPECIFICATIONS

Frequency	135 - 300 MHz (2M-BAND, PMR)
Bandwidth	15 MHz
Impedance	50 ohm
Vswr	< 2.0
Polarisation	Vertical
Gain	0 dBd, 2.1 dBi
Max. Input Power	200 W



## MECHANICAL SPECIFICATIONS

Color	Black
Height	Approx. 700 mm (Before cutting)
Weight	90 g
Mounting	On "G"-type mounts
Mounting Place	Vehicle roof
Mounting Instruction	Antenna must be cut to specified frequency. Cutting Table included
Materials	Stainless steel, PE and brass
Operating Temperature	-40C to +70C
Connector	M5 threaded stud

## Datasheet

2 / 2

## ORDERING INFORMATION

P/N	G12051
P/N	G12051IP (Bulk packing)

## PACKAGING INFORMATION

Type	Polybag or bulk
------	-----------------

