Datasheet

# G380-470 3 dB (M5)

Flexible collinear customer tunable antenna whip (380-470 MHz)

Flexible collinear customer tunable antenna whip especially made for use with "G"-type mounts (bases) (380-470 MHz) on vehicle roof etc.

- CUSTOMER TUNABLE (BY CUTTING)
- CUTTING TABLE FOR TUNING SUPPLIED

### **ELECTRICAL SPECIFICATIONS**

Frequency	380 - 470 MHz (TETRA, PMR, ISM)
Bandwidth	25 MHz
Impedance	50 ohm
Vswr	<1.5
Polarisation	Vertical
Gain	3 dBd, 5.1 dBi
Max. Input Power	80 W



### MECHANICAL SPECIFICATIONS

Color	Black
Height	Approx. 680 mm (Before cutting)
Weight	60 g
Mounting	On "G"-type mounts
Mounting Place	Vehicle roof
Mounting Instruction	Antenna must be cut to specified frequency. Cutting Table included
Materials	Stainless steel, PE and brass
Operating Temperature	-40C to +70C
	M5 threaded stud

Printed: 10/30/2025

## Datasheet

### ORDERING INFORMATION

P/N	G12039
P/N	G12039IP (Bulk packing)

### PACKAGING INFORMATION

