G380-470 3 dB (M5)

Flexible collinear customer tunable antenna whip (380-470 MHz)



Flexible collinear customer tunable antenna whip especially made for use with "G"-type mounts (bases) (380-470 MHz) on vehicle roof etc.

- CUSTOMER TUNABLE (BY CUTTING)
- CUTTING TABLE FOR TUNING SUPPLIED

ELECTRICAL SPECIFICATIONS

Frequency	380 - 470 MHz (TETRA, PMR, ISM)
Bandwidth	25 MHz
Impedance	50 ohm
Vswr	< 1.5
Polarisation	Vertical
Gain	3 dBd, 5.1 dBi
Max. Input Power	80 W

MECHANICAL SPECIFICATIONS

Color	Black
Height	Approx. 680 mm (Before cutting)
Weight	60 g
Mounting	On "G"-type mounts
Mounting Place	Vehicle roof
Mounting Instruction	Antenna must be cut to specified frequency. Cutting Table included
Materials	Stainless steel, PE and brass
Operating Temperature	-40C to +70C
Connector	M5 threaded stud

Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.

ORDERING INFORMATION

P/N	G12039
P/N	G12039IP (Bulk packing)

PACKAGING INFORMATION

Type	Polybag or bulk



Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.