

# UHF263

3 dB UHF Fibreglass Antenna 0.21 m (2500-2690 MHz)

- Antenna especially made for 4G/LTE
- End-fed  $1/2 \lambda$  coaxial dipole antenna design
- Full omni-directional radiation pattern
- No groundplane needed

## ELECTRICAL SPECIFICATIONS

Frequency	2500 - 2690 MHz
Bandwidth	100 MHz
Impedance	50 ohm
Vswr	<1.5
Polarisation	Vertical
Gain	3 dB (Marine), 0 dBd, 2.1 dBi
Max. Input Power	40 W



## Datasheet

2 / 4

## MECHANICAL SPECIFICATIONS

Color	White and chrome
Height	Approx. 210 mm
Weight	230 g
Mounting	On 1" threaded pole (G1"-11 thread) with Revolving Nut Kit or on optionally brackets
Mounting Place	On mast or deck
Materials	PU-painted glassfibre, PTFE and chromed solid brass
Survival Wind Speed	55 m/s (125 mph)
Operating Temperature	-55C to +70C (IEC 60068-2-1, IEC 60068-2-2)
Connector	N-female
Cable	No cable supplied
Ingress protection	IP66
Vibration	IEC 60068-2-6, IEC 60068-2-64
Serial no.	On product label

## ORDERING INFORMATION

P/N	14263-000 (Antenna only - bulk packing)
P/N	14263-001 (Antenna only - in Polybag)
P/N	14263-002 (Antenna only - in Carton tube)
P/N	14263-431 (Antenna + 1" Revolving Nut Kit - in Polybag)
P/N	14263-432 (Antenna + 1" Revolving Nut Kit - in Carton tube)

## PACKAGING INFORMATION

Type	Bulk packing or individually packing in Polybag or Carton tube (See "ORDERING INFORMATION")
size	Approx. 0.3 m
weight	Approx. 0.3 kg



