

## Datasheet

1 / 2

# MINI-PT QUAD 1/4 (SMA-RP)

Semi-flexible full  $1/4 \lambda$  multiband whip antenna with SMA-connector with reversed polarity

Semi-flexible full  $1/4 \lambda$  multiband whip antenna with integrated SMA-male connector with reversed polarity, especially made for portable and stationary wireless applications (M2M) in the GSM850/900/1800/1900 and DECT systems

## ELECTRICAL SPECIFICATIONS

Frequency	824 - 894 MHz, 890 - 960 MHz, 1710 - 1880 MHz, 1850 - 1990 MHz (GSM850/900/1800/1900/DECT)
Bandwidth	See "FREQUENCY"
Impedance	50 ohm
Vswr	< 2.0 @ f.res.
Polarisation	Vertical
Gain	0 dBd, 2.1 dBi
Max. Input Power	10/5 W



## MECHANICAL SPECIFICATIONS

Color	Black
Height	43 mm
Weight	6 g
Mounting Place	On modems etc.
Materials	PE, copper, brass and Teflon
Connector	SMA-male-RP

## ORDERING INFORMATION

14919	In Polybag
14919IP	Bulk Packing

## PACKAGING INFORMATION

Type	Bulk or Polybag
------	-----------------

Datasheet

