


HF701 TX/RX

7 m two-part LF/HF Fibreglass Antenna with 1"-14NF threaded base

- High quality 7 m high HF antenna for professional use
- Designed for GMDSS installations
- Rugged design
- Chrome plated solid brass joints
- Designed for mounting with 4-Way Mount and Upper Support Bracket (not supplied) for easy lay down function
- Side fed via open single wire
- Full omni-directional radiation pattern

ELECTRICAL SPECIFICATIONS

Frequency	1.4 - 30 MHz (MF and HF)
Polarisation	Vertical
Max. Input Power	1000 W PEP
Static Capacitance	80 pF
Insulation Resistance	10 GOhm
Electric Length	6820 mm




Datasheet

2 / 3

MECHANICAL SPECIFICATIONS

Color	White
Height	7 m
Weight	2.7 kg
Diameter	Ø 21 to Ø 5 mm
Mounting	On deck/wall with ratchet mount and upper support bracket (not supplied!)
Mounting Place	Deck/wall mounting
Mounting Instruction	Supplied
Materials	PU-painted heavy duty glass-fibre tubes and chromed solid brass
Survival Wind Speed	55 m/s (125 mph)
Operating Temperature	-55C to +70C (IEC 60068-2-1, IEC 60068-2-2)
Connector	Screw terminal
Cable	No cable supplied (Use open single wire)
Serial no.	On product label



ORDERING INFORMATION

P/N	13702-082
-----	-----------

PACKAGING INFORMATION

Type	Carton tube
size	Ø 60 x 4000 mm
weight	Approx. 4.6 kg



